

# Product data sheet





#### Information


Designation ERGOSOFT 135° angled grab bar, White Polyalu, tube Ø 33 mm

Reference 046225

# **Product advantages**

- + Non-slip and anti rotation grab bar.
- + Concealed fixings.
- + Corrosion resistant warranty.

### Description



Ergonomic grab bar.

Composite material: White synthetic resin + aluminium profile + taupe ergonomic notch.

Tube Ø 33 mm.

White flange border and central body. Non-slip and anti-rotation for the hand.

Stainless steel fixing screws included.

#### Technical characteristics

Dimensions
Diameter Ø
Material
Gross weight

Packaging

Color

Maximum Weight Capacity

Laboratory tests
Made in France
Maintenance
Guarantee

White

365 x 365 mm


33 mm Polyalu 1.120 kg

Plastic protection bag

225 kg yes yes 10 years

150 kg

Page 1/2





Gencod
Custom code
Technical sheet

Spare parts

3563390462256 7615200000

A55035800\_IND\_06

Ref. 046100, Polyalu cover plate. Ref. 046101, Bag of 3 stainless steel screws. Ref. 046288, Flange, cover plate and fixings.

## Fixing and maintenance advices

Recommended height for the horizontal part: 800 mm from the ground. Grab bars provide support and added safety if properly fitted in accordance with our technical instructions. Careful consideration and selection of the appropriate wall fixings according to the wall-mounted support is required to ensure the long life of your accessory. The use of stainless steel screws (Ø 4 mm) is highly recommended to prevent corrosion in damp environment. Before drilling, physically hold the product against the wall at desired position and mark the hole locations. All the fixing points must be respected. After installation and before use, make sure that all fixing screws are tightened securely. DO NOT use the grab bar as a step. DO NOT sit on or hang from the grab bar.

Fiche produit mise a jour le : 10/01/202