

Product data sheet



Ar sis
EVOLUTION




Information

| | |
|-------------|---|
| Designation | ARSIS hinged bar, 600 x 109 x 182 mm, White Epoxy-coated Aluminium, tube 38 x 25 mm |
| Reference | 048660 |

Product advantages

- + **Soft close system.**
- + **Elliptic tube for an improved grip.**
- + **Upgradeable product !**

Description



Concealed fixings.
Elliptical tube 38 x 25 mm in white epoxy-coated aluminium.
Wall flange, joint and side plates in white synthetic resin.

Wall fixings included.
Design coordinated with all ARSIS Comfort items.
Perfectly suitable for use in the hospitality industry.

Technical characteristics

| | |
|--------------|-----------------------|
| Finish | Epoxy-coated |
| Color | White |
| Dimensions | 600 x 109 x 182 mm |
| Diameter Ø | 38 x 25 mm |
| Material | Aluminum |
| Gross weight | 2.250 kg |
| Packaging | Cardboard box + label |

| | |
|------------------------|----------------------------------|
| CE Marking : safe load | 150 kg |
| Laboratory tests | 225 kg |
| Made in France | yes |
| Maintenance | yes |
| Guarantee | 10 years |
| Gencod | 3563390486603 |
| Custom code | 7615200000 |
| Technical sheet | A48960812_IND_04 |

Fixing and maintenance advices

Recommended height for the horizontal part : 800 mm from the ground. Hinged bars provide support and added safety if properly fitted in accordance with our technical instructions. Careful consideration and selection of the appropriate wall fixings according to the wall-mounted support is required to ensure the long life of your accessory. The use of stainless steel screws (Ø 4 mm) is highly recommended to prevent corrosion in damp environment. Before drilling, physically hold the product against the wall at desired position and mark the hole locations. All the fixing points must be respected. After installation and before use, make sure that all fixing screws are tightened securely. DO NOT use the hinged bar as a step. DO NOT sit on or hang from the grab bar. On wall not strong enough, 3 solutions: the free-standing pole ref: 048400, the support prop ref: 048610 or you can also install a backplate behind the wall.

Fiche produit mise à jour le : 10/01/2024