

Product data sheet





Information


Designation Hinged bar, 600 mm, White Epoxy-coated Aluminium, tube Ø 30 mm

Reference 048860

Product advantages

- + Raised position locking.
- + Reinforced aluminium tube.
- + Help to get up and stand.
- + Concealed fixings.

Description



White epoxy-coated aluminium tube \emptyset 30 mm. Synthetic resin flange. Vertical locking.

Technical characteristics

Finish
Color
Dimensions
Diameter Ø
Material
Gross weight

Packaging

CE Marking : safe load Laboratory tests Made in France Epoxy-coated White 600 mm 30 mm Aluminum 1.980 kg

Four-color process cardboard

150 kg 225 kg yes

Page 1/2



Maintenance Guarantee Gencod

Custom code Technical sheet yes 10 years 3563390488607 7615200000

A48860825 IND 04

Fixing and maintenance advices

Recommended height for the horizontal part: 800 mm from the ground. Hinged bars provide support and added safety if properly fitted in accordance with our technical instructions. Careful consideration and selection of the appropriate wall fixings according to the wall-mounted support is required to ensure the long life of your accessory. The use of stainless steel screws (Ø 4 mm) is highly recommended to prevent corrosion in damp environment. Before drilling, physically hold the product against the wall at desired position and mark the hole locations. All the fixing points must be respected. After installation and before use, make sure that all fixing screws are tightened securely. DO NOT use the hinged bar as a step. DO NOT sit on or hang from the grab bar. On wall not strong enough, 3 solutions: the free-standing pole ref: 048400, the support prop ref: 048810 or you can also install a backplate behind the wall.

Fiche produit mise à jour le : 10/01/2024