

# Product data sheet





#### Information


Designation Reference

Double towel rail, 538 x 69 x 67,5 mm, White Epoxy-coated Aluminium , tube 38 x 25 mm 049812

## **Product advantages**

- + Elegant and design shape.
- + Concealed fixings.
- + Corrosion resistant warranty.

## Description



2 fixed arms. Elliptical white aluminium tube 38 x 25 mm. White resin cover plates.

Wall fixings included. Design coordinated with all ARSIS Comfort items. Perfectly suitable for use in the hospitality industry.

#### **Technical characteristics**

| Finish         | Epoxy-coated                                |
|----------------|---|
| Color          | White                                       |
| Dimensions     | 535 x 70 x 67.5 mm                          |
| Diameter Ø     | 38 x 25 mm                                  |
| Material       | Aluminum                                    |
| Gross weight   | 0.460 kg                                    |
| Packaging      | Plastic protection bag + Hanger for display |
| Made in France | yes   |
| Maintenance    | yes   |
| Guarantee      | 5 years                                     |

PELLET ASC - ZI DE CHAPOTIN - 240 RUE DES FRÈRES VOISIN - CS 270048 - 69967 CHAPONNAY CEDEX - FRANCE - TEL : +33 (0)4 78 96 82 20 - FAX : +33 (0)4 78 96 70 52

© PELLET ASC – Non contractual document. Please read our General Sales Conditions. Dimensions in mm. All dimensions and specifications are given for information purposes only and can be changed without notice in order to improve our products.



Gencod Custom code Technical sheet Spare parts 3563390498125 7615200000 <u>\$04901100\_IND\_03</u> Réf. 049007 : Support de fixation alu chromé, Réf. 049008 : Cache-fixation blanc

#### Fixing and maintenance advices

The robe hooks are designed and manufactured for use assigned to them. These products may under no circumstances be used to maintain, recover or hang. Careful consideration and selection of the appropriate wall fixings according to the wall-mounted support is required to ensure the long life of your accessory. The use of stainless steel screws (Ø 4 mm) is highly recommended to prevent corrosion in damp environment. Before drilling, physically hold the product against the wall at desired position and mark the hole locations. All the fixing points must be respected. After installation and before use, make sure that all fixing screws are tightened securely.

Fiche produit mise à jour le : 10/01/2024