

# Product data sheet





#### Information

Designation


Reference

ARSIS 135° angled grab bar, 400 x 400 mm, White Epoxy-coated Aluminium, 3 fixing points 049835

#### **Product advantages**

- + Elliptic tube for an improved grip.
- + Possible to fit it "to the right" or "to the left".
- + Elegant and design shape.
- + Corrosion resistant warranty.

### Description



3 fixing points. Symmetrical 400 x 400 mm. Elliptical tube in white epoxy-coated aluminium. White resin cover plates. 3rd point to be fitted for right or left configuration.

Wall fixings included. Design coordinated with all ARSIS Comfort items. Perfectly suitable for use in the hospitality industry.

## **Technical characteristics**

Finish	Epoxy-coated
Color	White
Dimensions	400 x 400 mm
Diameter Ø	38 x 25 mm
Material	Aluminum
Gross weight	0.860 kg
Packaging	Plastic protection bag + Hanger for display
CE Marking : safe load	150 kg

PELLET ASC - ZI DE CHAPOTIN - 240 RUE DES FRÈRES VOISIN - CS 270048 - 69967 CHAPONNAY CEDEX - FRANCE - TEL : +33 (0)4 78 96 82 20 - FAX : +33 (0)4 78 96 70 52

© PELLET ASC - Non contractual document. Please read our General Sales Conditions. Dimensions in mm.

All dime ons and specifications are given for information purposes only and can be changed without notice in order to improve our products



Laboratory tests Made in France Maintenance Guarantee Net weight Gencod Custom code Technical sheet Spare parts 225 kg yes yes 10 years 0.800 kg 3563390498354 761520000 A04903502\_IND\_06 Réf. 049007 : Support de fixation alu chromé, Réf. 049008 : Cache-fixation blanc

#### Fixing and maintenance advices

Recommended height for the horizontal part : 800 mm from the ground. Grab bars provide support and added safety if properly fitted in accordance with our technical instructions. Careful consideration and selection of the appropriate wall fixings according to the wall-mounted support is required to ensure the long life of your accessory. The use of stainless steel screws (Ø 4 mm) is highly recommended to prevent corrosion in damp environment. Before drilling, physically hold the product against the wall at desired position and mark the hole locations. All the fixing points must be respected. After installation and before use, make sure that all fixing screws are tightened securely. DO NOT use the grab bar as a step. DO NOT sit on or hang from the grab bar.

Fiche produit mise à jour le : 10/01/2024