

# Product data sheet





#### Information


Designation Reference

Double robe hook, 105 x 69 x 67,5 mm, White epoxy-coated Aluminium, mat chrome-plated flanges, tube 38 x 25 mm 049911

## **Product advantages**

- + Elegant and design shape.
- + Concealed fixings.
- + Corrosion resistant warranty.

## Description



Elliptical white aluminium tube 38 x 25 mm. Mat chrome-plated resin cover plates.

Wall fixings included. Design coordinated with all ARSIS Comfort items. Perfectly suitable for use in the hospitality industry.

### **Technical characteristics**

Finish	Epoxy-coated
Color	Mat chrome-plated & white
Dimensions	105 x 70 x 67.5 mm
Diameter Ø	38 x 25 mm
Material	Aluminum
Gross weight	0.180 kg
Packaging	Plastic protection bag + Hanger for display
Made in France	yes
Maintenance	yes
Guarantee	5 years

PELLET ASC - ZI DE CHAPOTIN - 240 RUE DES FRÈRES VOISIN - CS 270048 - 69967 CHAPONNAY CEDEX - FRANCE - TEL : +33 (0)4 78 96 82 20 - FAX : +33 (0)4 78 96 70 52

© PELLET ASC – Non contractual document. Please read our General Sales Conditions. Dimensions in mm. All dimensions and specifications are given for information purposes only and can be changed without notice in order to improve our products.



Gencod Custom code Technical sheet Spare parts 3563390499115 7615200000 <u>S04901100 IND 03</u> Réf. 049007 : Support de fixation alu chromé, Réf. 049009 : Cache-fixation gris chromé mat

#### Fixing and maintenance advices

The towel rails are designed and manufactured for use assigned to them. These products may under no circumstances be used to maintain, recover or hang. Careful consideration and selection of the appropriate wall fixings according to the wall-mounted support is required to ensure the long life of your accessory. The use of stainless steel screws (Ø 4 mm) is highly recommended to prevent corrosion in damp environment. Before drilling, physically hold the product against the wall at desired position and mark the hole locations. All the fixing points must be respected. After installation and before use, make sure that all fixing screws are tightened securely.

Fiche produit mise à jour le : 10/01/2024